

## A synthetic oil.

A Low SAPS technology lubricant for Euro 4/5/6 engines, with particulate filter for diesel, and with catalytic converter for petrol, which ensures long service life and efficiency of after-treatment systems, and provides energy savings making it a more environmentally-friendly product.

#### **PERFORMANCES**

Standards: ACEA C3

API SN/CF

# **ORGANISATIONS & MANUFACTURERS - Scope of application -**

**ACEA C3:** requiring a "Low SAPS" oil (low sulfated ash content <0.8%, 0.07%<Phosphorus<0.09%, S<0.3%=ACEA C2), with HTHS viscosity >3.5 mPa.S and achieving the maximum oil change intervals specified by the engine manufacturer.

**API SN:** Designed to reduce high temperature deposits on the pistons and to minimise sludge formation under tough operating conditions. The product meets the requirements of ILSAC GF-5 by combining API SN performance levels with enhanced fuel economy.

API CF: Diesel, since 1994 (not recommended in the USA for light-duty vehicles).

Characteristics	Standards	Units	Values
Density at 15°C	ASTM D4052	g/cm³	0.852
Viscosity at 40°C	ASTM D445	mm²/s	71
Viscosity at 100°C	ASTM D445	mm²/s	12
Viscosity index	NF T 60-136	-	171
TBN	ASTM D2896	mg KOH/g	7.2
Sulfated ash content	ASTM D874	% m	0.77
Pour point	ASTM D2602	°C	-33
Flash point	ASTM D92	°C	234

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: I-124-1503 Published: 10/03/2020



# ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

## ГРАФИК РАБОТЫ:

Пн. - Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00 Вс.: с 10:00 по 16:00

## контакты:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара: <a href="https://storgom.ua/product/igol-171449.html">https://storgom.ua/product/igol-171449.html</a>

Другие товары: <a href="https://storgom.ua/motornye-masla.html">https://storgom.ua/motornye-masla.html</a>