

Special semi-synthetic lubricant for transmissions and transfer boxes for passenger cars and light trucks when API GL-4 / GL-4 +/GL-5 SAE 75W-80 lubricant is required.

IGOL RALLY GEAR 75W-80 can be used when API GL-5 lubricant is required.

PERFORMANCES

Standards:

API GL-4/GL-4+/GL-5

Specifications:

BMW MTF LT-2
BMW MTF LT-3
GM 1940182
GM 1940768
GM 1940764
MB 235.10
PSA B71 2330
Special gear oil, MTF 94
Special Honda MTF
Special Honda MTF-II
Tranself NFJ /TRJ /TRZ / TRT
Volvo 97308
Volvo 97309
VW G 009 317
VW G 052 178
VW G 052 512
VW G 060 726

Technical data sheet

ADVANTAGES

- Protects synchro from corrosion and deterioration.
- Ensures their lifespan. Compatible with elastomers.
- Brings real driving comfort compared to traditional oils.
- Allows an extension of the emptying spaces of the gearboxes while preserving them from the mechanical wear of the mechanical parts and the deterioration of the synchros.
- Particularly suitable for improving the operation of gearboxes with cold shifting problems.



USES

Recommended for the mechanical gearboxes of Peugeot, Citroën and Renault vehicles for 75W-80 grades.

Recommended for all transfer boxes.

Mini, Mercedes, Smart, Alfa Romeo, Fiat, Volvo, Honda, Rover, Citroen, Peugeot, Dacia, Renault, Seat, Skoda, Volkswagen.

Characteristics	Methods	Units	75W-80
Density at 15°C	NF T 60-101	kg/m ³	872
Kinematic viscosity at 40°C	NF T 60-100	mm ² /s	46
Kinematic viscosity at 100°C	NF T 60-100	mm ² /s	8.8
Viscosity index	NF T 60-136	-	174
Brookfield – 40°C	NF T 60-152	mPa.s	135000
Brookfield – 26°C	NF T 60-152	mPa.s	-
Pour point	NF T 60-105	°C	- 42
COC flash point	NF T 60-118	°C	>190

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: IV-01-1503
Published: 02/07/2018

Technical data sheet



ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

ГРАФИК РАБОТЫ:

Пн. – Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00

Вс.: с 10:00 по 16:00

КОНТАКТЫ:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара: <https://storgom.ua/product/igol-171523.html>

Другие товары: <https://storgom.ua/transmissionnye-masla.html>