



PROFIVE F913 5W-30

Synthetic oil.

New generation lubricant for Ford "Fuel Economy" petrol and Diesel engines with or without particle filters.

Suitable for Diesel and petrol fuels, biofuels and other fuels approved by the manufacturers.

PERFORMANCES

Standards: ACEA A5/B5 Specifications:

ACEA A1/B1 FORD WSS M2C-913D*
API SL/CF RENAULT RN0700

ORGANISATIONS & MANUFACTURERS - Scope of application -

ACEA A5/B5: For "High Performance Fuel Economy" Petrol and Diesel engines.

ACEA A1/B1: For Fuel Economy Petrol and Diesel engines.

API SL: Meets the requirements of modern engines from 2001 based on particular American Petroleum Institute specifications.

API CF: Diesel from 1994 (not recommended for LV in EU).

FORD WSS M2C-913D: for Petrol and Diesel engines with or without PF (5W30 factory fill and service fill). Can be used when the old Ford WSS-M2C-913C/- A and B specifications are requested.

RENAULT RN 700: for all RENAULT group engines, Turobocompressed Petrol Renault Sport and all Diesel 1.5L dCi engines without PF (<100CV), oil-change interval 20 000 Kms or 1 year.



^{*} Approved quality. Use recommended under manufacturers' warranties.



PROFIVE F913 5W-30

Characteristics	Standards	Unit	Values
Appearance			Bright & Clear
Colour			brown
Specific gravity at 15°C	ASTM D4052	g/cm3	0,845
Cinematic viscosity at 40°C	ASTM D7042	mm²/s	53,9
Cinematic viscosity at 100°C	ASTM D7042	mm²/s	9,8
Viscosity Index			170
Flash point	ASTM D92	°C	221
Pour point	ASTM D97	°C	-47
Noack volatility	ASTM D5800	%	11,8
Total Basic Number	ASTM D2896	mgKOH/g	9,45
CCS at -30°C	ASTM D5293	cР	3707
MRV at -35°C	ASTM D4684	сР	15 143
HTHS	ASTM D4683	сР	3,04
Sulfated ash		% mass	1,06

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference: I-119-1507 Date of issue: 28/02/2020



ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

ГРАФИК РАБОТЫ:

Пн. - Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00 Вс.: с 10:00 по 16:00

контакты:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара: https://storgom.ua/product/igol-171483.html

Другие товары: https://storgom.ua/motornye-masla.html