

# **PROCESS HYBRID 0W-20**

### Synthetic engine lubricant with low viscosity compatible with hybrid engines.

### PERFORMANCES

#### API SP:

The most restrictive level of API (American Petroleum Institute) standard for oils to meet the needs of new gasoline engine technologies: low speed pre-ignition (LSPI) and deposit formation.

### ILSAC GF-6A:

The ILSAC GF-6 specification is intended to protect newly designed engines that automotive equipment manufacturers produce to comply with emissions and fuel efficiency laws. The standard will ensure that approved oils provide superior protection and increased efficiency for engines.

### ADVANTAGES

**PROCESS HYBRID** helps to reduce fuel consumption and CO2 emissions, thus contributing to environmental protection.

The low viscosity of **PROCESS HYBRID** optimises lubrication at low temperatures, which facilitates cold starting and reduces wear.

Highly compatible with hybrid engines from North American and Asian manufacturers.





# **PROCESS HYBRID 0W-20**

### **PHYSICO-CHEMICAL PROPERTIES**

Characteristics	Standards	Unit	Values
Specific gravity at 15°C	ASTM D4052	g/cm <sup>3</sup>	0.842
Cinematic viscosity at 40°C	ASTM D7042	mm²/s	44
Cinematic viscosity at 100°C	ASTM D7042	mm²/s	8.4
Viscosity Index			172
HTHS	ASTM D4683	mPa.s	2.60
TBN	ASTM D2896	mgKOH/g	7.1
Pour point	ASTM D97	°C	-44
Flash point	ASTM D92	°C	228

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference: I-IGOL022-2104 Date of issue: 30/04/2021



IGOL France - 614, rue de Cagny - CS 19403 - 80094 Amiens CEDEX 3 - FRANCE - T. +33 (0)3 22 47 79 47 - F. +33 (0)3 22 46 79 61 - www.igol.com

# ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

## ГРАФИК РАБОТЫ:

Пн. – Пт.: с 8:30 по 18:30 Сб.: с 09:00 по 16:00 Вс.: с 10:00 по 16:00

## контакты:

+38 (044) 360-46-77 +38 (066) 77-395-77 +38 (097) 77-236-77 +38 (093) 360-46-77

Детальное описание товара: <u>https://storgom.ua/product/igol-171460.html</u> Другие товары: <u>https://storgom.ua/motornye-masla.html</u>