



VRLA Rechargeable Battery

MPL110-12 Standard Type



FEATURES

- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Low self-discharge rate,lower than 3% capacity loss per month
- Can be used in any orientation(excluding used inverted)
- The battery is designed with very lower resistance and exceeding high power performance
- Flame-arrestor is installed to ensure safety
- Absorbent Glass Mat technology for efficient gas recombination

APPLICATION

- UPS
- Telecom
- Golf-Carts
- Cable TV
- Power station
- Marine



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	108Ah @ 10 hour rate F.V.(1.75V/cell)
Approx. Weight	34.3Kg(75.62lbs.)
Terminals	B3 (Fitting M6 bolt & nut) I2 is optional
Internal Resistance	≤3mΩ (Fully Charged)
Max. Charge Current	32.4 A
Cold Cranking Amp @ -18°C	850 A
Short Circuit Current	2900 A
Operating Temperature Range	Charge : 0°C~50°C(32°F~122°F) Discharge : -20°C~60°C(-4°F~140°F) Storage. : -20°C~50°C(-4°F~122°F)
Container Material	Standard: PP(UL 94-HB) MPL110-12 Optional: Flame Retardant PP(UL 94-V0) MPL110-12FR

MH19884
 C4M20310-2474-E-16

 ● IEC60896-21/22
 ● JIS C 8704-2
 ● GB/T 19638.2

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
Length 330±2.0 (12.99±0.08) Width 173±2.0 (6.81±0.08) Container Height 212±2.0 (8.35±0.08) Total Height B3:241±2.0 (9.49±0.08) I2:218±2.0 (8.59±0.08)		<p>Terminal Hardware Initial Torque: B3,I2(5.5Nm±5%)</p>

Constant power discharge characteristics at 25 °C/77 °F Unit: W

Discharge Time / F.V. (V/cell)	5 Min	10 Min	15 Min	20 Min	25 Min	30 Min	40 Min	50 Min	60 Min	90 Min
1.80V	3810	2800	2326	1945	1685	1480	1192	1000	867	616
1.75V	4270	3005	2460	2020	1736	1518	1216	1021	880	626
1.70V	4554	3129	2545	2073	1770	1542	1233	1033	890	633
1.65V	4740	3225	2602	2112	1798	1560	1248	1044	898	638
1.60V	4880	3288	2640	2140	1820	1574	1260	1052	906	642

Constant current discharge characteristics at 25 °C/77 °F Unit: A

Discharge Time / F.V. (V/cell)	5 Min	10 Min	15 Min	20 Min	25 Min	30 Min	40 Min	50 Min	60 Min	90 Min
1.80V	354	246	202	166	142	123	99	83.1	72.8	51.7
1.75V	389	265	213	174	148	128	101	85.6	73.9	52.6
1.70V	414	276	220	178	152	131	104	86.8	74.8	53.2
1.65V	430	285	226	182	154	133	105	88.0	75.5	53.7
1.60V	444	290	230	185	156	134	106	88.0	76.0	54.0

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.

ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

ГРАФИК РАБОТЫ:

Пн. – Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00

Вс.: с 10:00 по 16:00

КОНТАКТЫ:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара:

<https://storgom.ua/product/akkumulyatornayabataryabbatterymp110-12b6.html>

Другие товары: <https://storgom.ua/akkumulatory-dlia-ibp.html>