

An oil for lubricating 4-stroke petrol engines in mechanised gardening equipment, particularly Honda brand.

PERFORMANCES

Standards:

API SL
API SM

ADVANTAGES

Good detergent and dispersant properties which keep the engine perfectly clean, by preventing deposits and varnish on segments and pistons.

Characteristics	Standards	Units	Values
Viscosity at 40°C	ASTM D445	mm ² /s	69.2
Viscosity at 100°C	ASTM D445	mm ² /s	10.5
Viscosity index	NF T 60-136	-	139
Density at 15°C	ASTM D1298	kg/m ³	878
COC flash point	ASTM D92	°C	230

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: I-114-1503
Published: 06/07/2022

Technical data sheet

ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

ГРАФИК РАБОТЫ:

Пн. – Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00

Вс.: с 10:00 по 16:00

КОНТАКТЫ:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара: <https://storgom.ua/product/igol-171471.html>

Другие товары: <https://storgom.ua/motornye-masla-dlya-sadovoj-tehniki.html>