

An anti-smoke lubricant for 2-stroke engines in chainsaws, tillers and mowers.

PERFORMANCES

Standards:

JASO-FC Anti-smoke

ADVANTAGES

This formulation offers an environmentally friendly outlook while guaranteeing excellent performances thanks to:

- A choice of oily and viscous synthetic bases with low smoke emissions.
- A high-performance additive system focused on engine cleanliness by reducing and eliminating deposits.

Compatible with all fuels.

USES

Perfectly tailored to separate greasing of engines, or mixed greasing on small and medium-capacity engines.

In mixture, use 2 % to 4 % (according to manufacturer's recommendations).

Fuel	Dose 2% (50:1)	Dose 3% (33:1)	Dose 4% (25:1)
1 litre	20 ml	30 ml	40 ml
2 litres	40 ml	60 ml	80 ml
5 litres	100 ml	150 ml	200 ml
10 litres	200 ml	300 ml	400 ml

Characteristics	Methods	Units	Values
Colour	visual	-	Red
Density at 15°C	NF T 60-101	kg/m ³	878
Kinematic viscosity at 100°C	NF T 60-100	mm ² /s	9.59
Viscosity index	NF T 60-136	-	129
COC flash point	NF T 60-118	°C	>100

The characteristics are given purely for information and are consistent with our current production standards. IGOL reserves the right to modify them, in order to pass on technical developments to its customers. Before using this product, you should consult the instructions for use and the environmental impact shown on the technical and safety data sheets. The information given above is based on the current state of our knowledge of the product in question. The product user should take all relevant precautions relating to its use. Under no circumstances may IGOL be held liable for damages resulting from misuse.

Document ref.: II-54-1503
Published: 26/07/2016

ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

ГРАФИК РАБОТЫ:

Пн. – Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00

Вс.: с 10:00 по 16:00

КОНТАКТЫ:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара: <https://storgom.ua/product/igol-171475.html>

Другие товары: <https://storgom.ua/motornye-masla-dlya-sadovoj-tehniki.html>