


AD 410

Doosan
Mecc Alte
D+ &



ISO8528

GC,) &

SZUTEST

GC - \$\$\$



2000/14/EC

&\$\$\$#(#

z) \$ z' z' D:

| | " | " | " | " | Amp |
|---------|--------|--------|--------|--------|--------|
| 400/230 | 410,00 | 328,00 | 375,00 | 300,00 | 541,00 |

fP GDE

GC,) &

,) & z

fDF DE

%\$!

% %&

GC" \$(**

z&(

GC

Standard Specifications

z

fl

E

z

z

ALTERNATOR

D: A Z 5J F

TRANSFER SWITCH

AD 410

Doosan
Mecc Alte
D+' &'

| | | | | | | | | | | | | | | | | |
|--------------------------------------|--------|---|-------|-------|-------------|--|--|--|--------------|--|--|--|-----------------|--|--|--|
| Manufacturer | | Doosan | | | | | | | | | | | | | | |
| Model | | P158LE-1 | | | | | | | | | | | | | | |
| | | <table border="1"> <tr> <td>%\$\$' "# "</td> <td></td> <td></td> <td></td> </tr> <tr> <td>' * &\$\$' "</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Q,) \$\$\$< DQ</td> <td></td> <td></td> <td></td> </tr> </table> | | | %\$\$' "# " | | | | ' * &\$\$' " | | | | Q,) \$\$\$< DQ | | | |
| %\$\$' "# " | | | | | | | | | | | | | | | | |
| ' * &\$\$' " | | | | | | | | | | | | | | | | |
| Q,) \$\$\$< DQ | | | | | | | | | | | | | | | | |
| | L | 14,600 | | | | | | | | | | | | | | |
| | " | 128 x 142 | | | | | | | | | | | | | | |
| | | 15,0:1 | | | | | | | | | | | | | | |
| | fl # ı | "# " | 1500 | | | | | | | | | | | | | |
| | fl ı | L | 21,00 | | | | | | | | | | | | | |
| | | L | 88,50 | | | | | | | | | | | | | |
| AbsorbedAirDischargeReSourceKey.Text | ' # " | 23,50 | | | | | | | | | | | | | | |
| fl ' # ı | ' # " | 410,00 | | | | | | | | | | | | | | |
| | ' # " | 59,50 | | | | | | | | | | | | | | |
| | ° C | 520,00 | | | | | | | | | | | | | | |
| | | 24 V d.c. | | | | | | | | | | | | | | |
| | Load | %\$\$ı | '+)ı |)\$ı | | | | | | | | | | | | |
| | # " | 78,70 | 58,40 | 40,00 | | | | | | | | | | | | |

| | | | | |
|-------------|------|-------------|--|--|
| | | Mecc Alte | | |
| | | ECO 40-1S/4 | | |
| | Hz | 50 | | |
| | " | 400,00 | | |
| 7cg' | | 0,80 | | |
| | | 3 | | |
| | fl ı | 400/230 | | |
| | A | 577,00 | | |
| Temperature | | H | | |

| | | fl ı | | fl ı | |
|--------|---------|---------|---------|---------|--------|
| | " | " | " | " | L |
| AD 410 | 3030,00 | 2965,00 | 1550,00 | 1994,00 | 700,00 |
| | | fl ı | | fl ı | |
| | " | " | " | " | L |
| MS 70 | 4024 | 4400 | 1560 | 2360 | 700 |

AD 410

Doosan
Mecc Alte
D+ &



f@z@Bl
f@z@Bl

"z" "z"

f@z@Bl

971

#

#

#

#



f&%) +L

f&)(, L

f&%) \$L

6G'9B '* \$-) \$

6G'9B '* \$\$\$! *!&

6G'9B '* \$\$\$! *!(

#



ž

%, !&*(

&(\$)

ž

ž

GA 8

!&+""

ž

AD 410

Doosan
Mecc Alte
D+ &



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

| | | |
|-------|---|------|
| | " | 1560 |
| fl "L | " | 4400 |
| fl "L | " | 2360 |
| | L | 700 |

ОФИЦИАЛЬНЫЙ ДИЛЕР В УКРАИНЕ:

storgom.ua

ГРАФИК РАБОТЫ:

Пн. – Пт.: с 8:30 по 18:30

Сб.: с 09:00 по 16:00

Вс.: с 10:00 по 16:00

КОНТАКТЫ:

+38 (044) 360-46-77

+38 (066) 77-395-77

+38 (097) 77-236-77

+38 (093) 360-46-77

Детальное описание товара: <https://storgom.ua/product/dizelnyi-generator-aksa-ad4-0.html>

Другие товары: <https://storgom.ua/dizelnye-generatory.html>